

Patent Protection & Registration

[Patents](#) grant property rights on new and useful inventions, allowing the patent holder to prevent others from using, making, or selling that invention without permission for a limited time. U.S. patents are permitted by the U.S. Constitution and are designed to promote scientific progress and invention. By allowing inventors to profit from licensing or selling their patent rights, inventors can recoup their research and development costs and benefit financially from their inventing efforts. There are three main types of patents utility, plant, and design. Utility and plant patents can last up to 20 years, while design patents can last up to 15 years. When a patent expires, the patented material enters the public domain, making it free to use by anyone without a license. U.S. patents are issued by the [United States Patent and Trademark Office \(USPTO\)](#).

U.S. Patent No. 12,000,200 entitled “Furniture Connecting Fitting” issued June 4, 2024 to Samet Kalip Ve Madeni Esya San Ve Tic. A.S. of Istanbul, Turkey. Invented by Artur Hirtsiefer of Neunkirchen-Seelscheid, Turkey. Abstract: The invention relates to a furniture connecting fitting, in particular a hinge, preferably a hatch holder, wherein the furniture connecting fitting has a kinematic arrangement (30) with levers and links, and by means of which kinematic arrangement a door or a hatch can be moved from a closed position to an open position, wherein an actuating arrangement (70) acts at the kinematic arrangement (30), wherein the actuating arrangement (70) comprises an actuator (72) and a holder (73), which can be adjusted relative to the actuator (72), wherein the actuator (72) can be moved by a part of the kinematic arrangement (30) and the holder (73) is supported relative to an attachment section (51, 53) or an additional component of the kinematic arrangement (30); in the case of such a furniture connecting fitting, the user is offered a wide range of applications with a small number of parts if provision is made that, in a first mode of operation, the actuating arrangement (70) acts using a damper (71) in a damping manner between the actuator (72) and the holder (73) and, in a second mode of operation, a spring force acting counter to the damping direction is applied directly or indirectly to the actuator (72) and the holder (73) by means of a tension spring (74).